


AI in the Sciences and Engineering HS 2025: Lecture 3

Siddhartha Mishra

Computational and Applied Mathematics Laboratory (CamLab)
Seminar for Applied Mathematics (SAM), D-MATH (and),
ETH AI Center (and) Swiss National AI Institute (SNAI) ,
ETH Zürich, Switzerland.

Key Aim of this Course: Learn Physics modeled by PDEs from data using Neural Networks

Finite Difference Schemes (FDS) for the Heat Equation



- ▶ Heat equation is $u_t = u_{xx}$, Initial conditions: $u(x, 0) = \bar{u}(x)$, Boundary conditions: $u(0, t) = u(1, t) = 0$.
- ▶ $u_t(x_j, t^n) \approx \frac{v_j^{n+1} - v_j^n}{\Delta t}$, $u_{xx} \approx \frac{v_{j+1}^n - 2v_j^n + v_{j-1}^n}{\Delta x^2}$
- ▶ Finite Difference Scheme:

$$v_j^{n+1} = (1 - 2\lambda)v_j^n + \lambda(v_{j-1}^n + v_{j+1}^n), \quad \lambda = \frac{\Delta t}{\Delta x^2}$$

Can Neural Networks be used to solve PDEs without any Data ?

Can Neural Networks be used to solve PDEs without any Data ?

- **Physics-Informed Neural Networks (PINNs)**

Physics Informed Neural Networks

- ▶ Variants of PINNs stem from [Dissanayake, Phan-Thien](#), 1994.
- ▶ Also in [Lagaris](#) et al, mid 1990s.
- ▶ Reintroduced by [Raissi, Perdikaris, Karniadakis](#), 2017.
- ▶ 10000s of papers on PINNs already.


Heat Eqn: $u_t = u_{xx}$ with 0-BC and $u(x, 0) = \bar{u}(x)$ IC

- ▶ Deep Neural networks : $(x, t) \mapsto u_\theta(x, t)$, $\theta \in \Theta$.
- ▶ Temporal boundary residual: $\mathcal{R}_{tb,\theta} = u_\theta(\cdot, 0) - \bar{u}$
- ▶ Spatial boundary residual: $\mathcal{R}_{sb,\theta} = u_\theta|_{\partial D}$.
- ▶ Interior PDE Residual: $\mathcal{R}_{int,\theta} = \partial_t u_\theta - \partial_{xx} u_\theta$
- ▶ Evaluate **PDE Residual** by Automatic Differentiation
- ▶ **Error (Mismatch)**:

$$\begin{aligned}\hat{J}(\theta) := & \int_0^T \int_D |\mathcal{R}_{int,\theta}(x, t)|^2 dx dt + \int_D |\mathcal{R}_{tb,\theta}(x)|^2 dx \\ & + \int_0^T \int_{\partial D} |\mathcal{R}_{sb,\theta}(x, t)|^2 ds(x) dt\end{aligned}$$

PINNs for Heat Equation (Contd..)

- ▶ Replace Integrals by **Quadrature**
- ▶ Collocation Point Cloud: $\mathcal{S} = \mathcal{S}_{int} \cup \mathcal{S}_{tb} \cup \mathcal{S}_{sb}$ **Randomly** chosen.



- ▶ Replacing integrals with Quadrature Rules $\Rightarrow$
- ▶ PINNs are trained by minimizing the **Loss Function**:

$$J(\theta) = \frac{1}{N_{tb}} \sum_{n=1}^{N_{tb}} |\mathcal{R}_{tb,\theta}(x_n)|^2 + \frac{1}{N_{sb}} \sum_{n=1}^{N_{sb}} |\mathcal{R}_{sb,\theta}(x_n, t_n)|^2 \\ + \frac{1}{N_{int}} \sum_{n=1}^{N_{int}} |\mathcal{R}_{int,\theta}|^2.$$

Why PINNs are great ?

- ▶ Very easy to Code !!
- ▶ A few lines in **PyTorch** or **JAX**

```
def compute_res(self, network, x_f_train):
    x_f_train.requires_grad = True
    u = network(x_f_train).reshape(-1, )
    grad_u = torch.autograd.grad(u, x_f_train, grad_outputs=torch.ones(x_f_train.shape[0], ).to(self.device), create_graph=True)[0]
    grad_u_t = grad_u[:, 0]
    grad_u_x = grad_u[:, 1]
    grad_u_xx = torch.autograd.grad(grad_u_x, x_f_train, grad_outputs=torch.ones(x_f_train.shape[0], ).to(self.device), create_graph=True)[0][:, 1]

    residual = grad_u_t - self.v * grad_u_xx
    return residual
```

Results for Multi-d Heat Eqn with Random points

- PINN with Depth 4, Width 20, Interior training points 2^{16} , Boundary points 2^{15}

Dimension	Training Error	Total Error
1	2.8×10^{-5}	0.0035%
5	0.0002	0.016%
10	0.0003	0.03%
20	0.006	0.79%
50	0.006	1.5%
100	0.004	2.6%

- No **Curse of dimensionality** !!

PDEs in Finance (Tanios, 2021)

- Black-Scholes type PDE with Uncorrelated Noise:

Dimension	Training Error	Generalization error
20	0.0016	1.0%
50	0.0031	1.5%
100	0.0031	1.8%

- Heston option-pricing PDE


Dimension	Training Error	Total Error
20	0.0064	1.0%
50	0.0037	1.3%
100	0.0032	1.4%

Viscous scalar conservation laws

- Nonlinear hyperbolic-parabolic PDE.

$$\begin{aligned}u_t + \operatorname{div} f(u) &= \nu \Delta u \quad (x, t) \in D \times [0, T], \\u(x, 0) &= \bar{u}(x), \quad x \in D, \quad u|_{\partial D} = 0.\end{aligned}$$

- Training set: $\mathcal{S} = \mathcal{S}_{int} \cup \mathcal{S}_{tb} \cup \mathcal{S}_{sb}$




- ▶ Deep Neural networks : $(x, t) \mapsto u_\theta(x, t)$, $\theta \in \Theta$.
- ▶ **Residuals**
 - ▶ Interior Residual: $\mathcal{R}_{int,\theta} = \partial_t u_\theta + \text{div } f(u_\theta) - \nu \Delta u_\theta$.
 - ▶ Temporal boundary residual: $\mathcal{R}_{tb,\theta} = u_\theta(\cdot, 0) - \bar{u}$
 - ▶ Spatial boundary residual: $\mathcal{R}_{sb,\theta} = u_\theta|_{\partial D}$.
- ▶ **Loss function:**


$$J = \underbrace{\sum_{n=1}^{N_{tb}} w_n^{tb} |\mathcal{R}_{tb,\theta}(x_n)|^2}_{(\mathcal{E}_T^{tb})^2} + \underbrace{\sum_{n=1}^{N_{sb}} w_n^{sb} |\mathcal{R}_{sb,\theta}|^2}_{(\mathcal{E}_T^{sb})^2} + \underbrace{\sum_{n=1}^{N_{int}} w_n^{int} |\mathcal{R}_{int,\theta}|^2}_{(\mathcal{E}_T^{int})^2}.$$

Results for 1-D Burgers' with Compression

- Sobol points, $N_{int} = 8192$, $N_{tb} = N_{sb} = 256$, Depth 8, Width 20.



$\nu = 10^{-2}$



$\nu = 10^{-3}$

Viscosity	Training Error	Total error
10^{-2}	0.0005	1.0%
10^{-3}	0.0008	1.2%

Incompressible Navier-Stokes equations

- **Nonlinear** PDE of form





$$\begin{aligned}u_t + (u \cdot \nabla)u + \nabla p &= \nu \Delta u + f, \quad (x, t) \in D \times [0, T], \\ \operatorname{div} u &= 0, \quad (x, t) \in D \times [0, T], \\ u(x, 0) &= \bar{u}(x), \quad x \in D, \quad u|_{\partial D \times (0, T)} = 0.\end{aligned}$$

- Training set: $\mathcal{S} = \mathcal{S}_{int} \cup \mathcal{S}_{tb} \cup \mathcal{S}_{sb}$


- ▶ Deep Neural networks : $(x, t) \mapsto u_\theta(x, t), p_\theta(x, t), \theta \in \Theta$.
- ▶ **Residuals**
 - ▶ Velocity Residual: $\mathcal{R}_{u,\theta} = \partial_t u_\theta + (u_\theta \cdot \nabla) u_\theta + \nabla p_\theta - f$
 - ▶ Divergence Residual: $\mathcal{R}_{div,\theta} := \text{div } u_\theta$
 - ▶ Temporal and Spatial boundary residuals as before.
- ▶ **Loss function:**

$$\begin{aligned}
 J(\theta) = & \underbrace{\sum_{n=1}^{N_{tb}} w_n^{tb} |\mathcal{R}_{tb,\theta}(x_n)|^2}_{(\mathcal{E}_T^{tb})^2} + \underbrace{\sum_{n=1}^{N_{sb}} w_n^{sb} |\mathcal{R}_{sb,\theta}|^2}_{(\mathcal{E}_T^{sb})^2} \\
 & + \underbrace{\sum_{n=1}^{N_{int}} w_n^{int} |\mathcal{R}_{u,\theta}|^2}_{(\mathcal{E}_T^u)^2} + \underbrace{\sum_{n=1}^{N_{int}} w_n^{int} |\mathcal{R}_{div,\theta}|^2}_{(\mathcal{E}_T^d)^2}
 \end{aligned}$$

Results for 2-D Taylor vortex




Results for 2-D Double Shear Layer




PINNs for nonlinear Dispersive PDEs


- Numex in [Bai, Koley, SM, Molinaro, 2021](#).



KdV



6-d param KdV



Benjamin-Ono


PDE	Network Size	Error
KdV	32×4	0.1%
6-D param KdV	24×8	0.5%
Benjamin-Ono	20×4	0.7%

Parametric PDEs

- ▶ Consider the **KdV** Eqn:

$$u_t + uu_x + u_{xxx} = 0,$$
$$u(0, x, y) = u_0(x, y).$$

- ▶ $y \in Y \subset \mathbb{R}^6$ **Parametrizes** Initial conditions.
- ▶ PINN: $(t, x, y) \mapsto u_\theta(t, x, y)$
- ▶ Visualizations of Mean + Variance.




- ▶ Error of 0.5%

Role of Data in PINNs

- ▶ PINNs for PDE Forward Problem require **NO** labelled Data
- ▶ If **small Data** is available $\Rightarrow$ better empirical performance.
- ▶ Relevant for parametrized PDEs
- ▶ Situation is different for **Inverse Problems** for PDEs.
- ▶ Data is a part of such problems !!

Data Assimilation or Unique continuation problem







- ▶ Abstract PDE is $\mathcal{D}(u) = f$ in $\mathbb{D}$
- ▶ **Measurements:** $\mathcal{L}(u) = g$ in $\mathbb{D}'$
- ▶ Goal: **Reconstruct** u given f, g .
- ▶ $u_\theta : \mathbb{D} \mapsto \mathbb{R}^m$ is a **PINN**
- ▶ **PDE Residual:** $\mathcal{R} := \mathcal{R}_\theta(y) = \mathcal{D}(u_\theta(y)) - f(y), y \in \mathbb{D}$
- ▶ **Data Residual:** $\mathcal{R}_d := \mathcal{R}_{d,\theta}(z) = \mathcal{L}(u_\theta(z)) - g(z), z \in \mathbb{D}'$.
- ▶ **PINNs** are minimizers of $\int_{\mathbb{D}} |\mathcal{R}_\theta(y)|^{p_y} dy + \int_{\mathbb{D}'} |\mathcal{R}_{d,\theta}(z)|^{p_z} dz$

- Model **Elliptic** PDE with Data assimilation problem:

$$\begin{aligned} -\Delta u &= f, & \text{in } \mathbb{D} \subset \mathbb{R}^d, \\ u|_{\mathbb{D}'} &= g & \text{in } \mathbb{D}' \subset \mathbb{D}. \end{aligned}$$

Results in 2-D



Results in 2-D

- No Noise: Depth 4, Width 24

N	Training Error	Generalization error
20^2	0.0008	1.1%
40^2	0.0006	1.0%
80^2	0.0005	0.9%
160^2	0.0004	0.8%





- With 1% noise:

N	Training Error	Generalization error
20^2	0.012	2.3%
40^2	0.013	1.9%
80^2	0.013	1.7%
160^2	0.013	1.3%

- Model **Parabolic** PDE with Data assimilation problem:

$$\begin{aligned}u_t - \Delta u &= f, \quad \text{in } D_T = D \times (0, T), \\u|_{\partial D} &= 0, \\u|_{D'_T} &= g \quad \text{in } D'_T \subset D_T\end{aligned}$$

Results



Results with Random points

- 1-D : Depth 4, Width 24

N	Training Error	Generalization error
16×50	0.001	0.55%
16×100	0.0009	0.52%
16×200	0.0007	0.47%


- Multi-D with $N = 2^{14}$ training points

Dimension	Training Error	Generalization error
5	0.0003	0.044%
10	0.0003	0.07%
20	0.0003	0.62%
50	0.0003	1.68%
100	0.0003	2.0%

- ▶ Model **Indefinite** PDE with Data assimilation problem:







$$\begin{aligned}\Delta u + \nabla p &= f, \quad \text{in } \mathbb{D} \subset \mathbb{R}^d, \\ u|_{\mathbb{D}'} &= g \quad \text{in } \mathbb{D}' \subset \mathbb{D}.\end{aligned}$$

2-D Results



N	Training Error	$\mathcal{E}_G(u)$	$\mathcal{E}_G(p)$
20^2	0.0007	2.3%	5.6%
40^2	0.0004	1.7%	4.0%
80^2	0.0004	1.5%	3.5%

2-D Results







Radiative Transfer Equations

- ▶ $2d + 1$ -dim **Integro-Differential** PDE for **Intensity**

$$\frac{1}{c} u_t + \omega \cdot \nabla u + (k(x, \nu) + \sigma(x, \nu)) u - \frac{\sigma(x, \nu)}{s_d} \int_{R_+} \int_S \Phi(\omega, \omega', \nu, \nu') u d\omega' d\nu' = f(x, t, n, \nu).$$

- ▶ **High-dimensional, non-local, hyperbolic, multiphysics**
- ▶ PINNs applied and bound derived in **SM, Molinaro** 2021.

Numerical Results for Forward Problem



2-D, Intensity

2-D, Boundary

6-D, Inc. Radiation

6-D, Radial flux

Dimension	Network Size	Error	Training Time
2	24×8	0.3%	57 min
6	20×8	2.1%	66 min

PINNs for Inverse Problem: Parameter Identification


- For Radiative Transfer Eqns:

$$\frac{1}{c}u_t + \omega \cdot \nabla u + (k(x, \nu) + \sigma(x, \nu)) u - \frac{\sigma(x, \nu)}{s_d} \int_{R_+} \int_S \Phi(\omega, \omega', \nu, \nu') u d\omega' d\nu' = f(x, t, n, \nu).$$


- Find Absorption Coefficient k , given Incident Radiation G
- PINNs with Tikhonov Regularization :SM, Molinaro, 2020

- For a 5-dimensional Radiative Transfer:

M	k -Error	u -Error	Training Time
20×8	2.8%	0.7%	104 min



Incident Radiation



Absorption Coefficient.